

Citroen Jumpy

Twin side door



Food delivery,
catering and biomedical transport



PolarLine[®]
by Novaplast



Fast & Easy
installation



NOVAPLAST[®]
thermo-insulated solutions

UNI EN ISO 9001 : 2015
UNI EN ISO 14001 : 2015



Citroen Jumpy

Twin side door

Wheelbase (mm)
Roof
Volume (m3)
Load floor length (mm)
Load floor width (mm)*
Load floor height (mm)*
Side door width (mm)
Side door height (mm)
Rear door width (mm)
Rear door height (mm)
Width between wheel arches

*(min/max)

Medium	Long
3.275	3.275
Low	Low
3,28	3,90
2.070	2.440
1.205/1.430	1.205/1.430
1.180/1.220	1.180/1.220
810	810
1.080	1.080
1.205	1.205
1.130	1.130
1.205	1.205

FEATURES

- Polyurethane foam panels, thickness 60mm
- Wood-reinforced floor
- Grey non-skid "tub" floor
- Reinforced roof for refrigeration unit application
- **Right and left side door**
- Double seal on rear and side doors

ACCESSORIES

- LED lights
- Walls reinforced for shelves
- Drain valve with drain pipe
- Anti-drip edges on the doors
- VTR liquid collection reservoir
- Cargo restraint profiles with straps
- Customizable setups upon request

