

Fiat Scudo

PolarLine[®]
by Novaplast



Food delivery,
catering and biomedical transport



Fast & Easy
installation



NOVAPLAST[®]
thermo-insulated solutions

UNI EN ISO 9001:2015
UNI EN ISO 14001:2015



Wheelbase (mm)
Roof
Volume (m3)
Load floor length (mm)
Load floor width (mm)*
Load floor height (mm)*
Side door width (mm)
Side door height (mm)
Rear door width (mm)
Rear door height (mm)
Width between wheel arches

*(min/max)

Medium	Long
3.275	3.275
Low	Low
3,28	3,90
2.070	2.440
1.205/1.430	1.205/1.430
1.180/1.220	1.180/1.220
810	810
1.080	1.080
1.205	1.205
1.130	1.130
1.205	1.205

FEATURES

- Polyurethane foam panels, thickness 60mm
- Wood-reinforced floor
- Grey non-skid "tub" floor
- Reinforced roof for refrigeration unit application
- Double seal on rear and side doors
- Suitable for IR transport (-20°C) with the application of high density polyurethane

ACCESSORIES

- LED lights
- Walls reinforced for shelves
- Roof and wall construction for transporting meats with stainless steel rails and hooks
- Drain valve with drain pipe
- Anti-drip edges on the doors
- VTR liquid collection reservoir
- Cargo restraint profiles with straps
- Additional rear and side doors (-20 °C)
- Customizable setups upon request

