

Ford Custom

TWIN SIDE DOOR



Food delivery, catering
and biomedical transport



PolarLine[®]
by Novaplast



Fast & Easy
installation



NOVAPLAST[®]
thermo-insulated solutions

UNI EN ISO 9001 : 2015
UNI EN ISO 14001 : 2015



Ford Custom

twin side door

Wheelbase (mm)
Roof
Volume (m3)
Load floor width (mm)*
Load floor length (mm)*
Load floor height (mm)*
Side door width (mm)
Side door height (mm)
Rear door width (mm)
Rear door height (mm)
Width between wheel arches

SHORT	LONG
3.100	3.500
LOW	LOW
4,5	5
2.280/2.210	2.680/2.610
1.660/1.360	1.660/1.360
1.245	1.245
870/920	870/920
1.250	1.250
1.080/1.230	1.080/1.230
1.250	1.250
1.230	1.230

FEATURES

- Polyurethane foam panels, thickness 60mm
- Wood-reinforced floor
- Grey non-skid "tub" floor
- Reinforced roof for refrigeration unit application
- Right and left side doors
- Double seal on rear and side doors



ACCESSORIES

- LED lights
- Walls reinforced for shelves
- Drain valve with drain pipe
- Anti-drip edges on the doors
- VTR liquid collection reservoir
- Cargo restraint profiles with straps
- Customizable setups upon request

