

Ford Custom

PolarLine[®]
by Novaplast



Fast & Easy
installation



Food delivery,
catering and biomedical transport



NOVAPLAST
thermo-insulated solutions

UNI EN ISO 9001 : 2015
UNI EN ISO 14001 : 2015



Wheelbase (mm)
Roof
Volume (m3)
Load floor length (mm)*
Load floor width (mm)*
Load floor height (mm)
Side door width (mm)*
Side door height (mm)
Rear door width (mm)*
Rear door height (mm)
Width between wheel arches

*(min/max)

L1	L2
3.100	3.500
Low	Low
4,5	5
2.280/2.210	2.680/2.610
1.660/1.360	1.660/1.360
1.245	1.245
870/920	870/920
1.250	1.250
1.080/1.230	1.080/1.230
1.250	1.250
1.230	1.230

FEATURES

- Polyurethane foam panels, thickness 60mm
- Wood-reinforced floor
- Grey non-skid "tub" floor
- Reinforced roof for refrigeration unit application
- Double seal on rear and side doors
- Suitable for IR transport (-20°C) with the application of high density polyurethane

ACCESSORIES

- LED lights
- Walls reinforced for shelves
- Roof and wall construction for transporting meats with stainless steel rails and hooks
- Drain valve with drain pipe
- Anti-drip edges on the doors
- VTR liquid collection reservoir
- Cargo restraint profiles with straps
- Additional rear and side doors (-20 °C)
- Customizable setups upon request

