

Mercedes Sprinter

PolarLine[®]
by Novaplast



Food delivery,
catering and biomedical transport



Fast & Easy
installation



NOVAPLAST[®]
thermo-insulated solutions

UNI EN ISO 9001 : 2015
UNI EN ISO 14001 : 2015





	L2H2	L3H2
Wheelbase (mm)	3665	4325
Roof	High	High
Volume (m³)	9	11,8
Loading floor width (mm)*	1360/1710	1360/1710
Loading floor length (mm)	3190	4200
Loading floor height (mm)	1780	1780
Side door width (mm)	1230	1230
Side door height (mm)	1720	1720
Rear door width (mm)*	1250/1450	1250/1450
Rear door height (mm)	1710	1710
Width between wheel arches	1220	1220

*(min/max)

FEATURES:

- Tub-shaped, anti slip grey floor
- Floor reinforced with wood layer
- Roof reinforced with wood for cooling unit installation
- Double seal on side and rear doors
- Suitable for transportation at -20°C with high density polyurethane and additional materials
- Self-supporting architecture of the internal cell.
The panels are not glued to the van body and can be easily dismantled for body repair work in case of road accident.

ACCESSORIES:

- LED light
- Reinforced walls for shelves installation
- Reinforced walls and roof with stainless steel plug
- Anti-drip edges on doors for fish or dairy transport
- Profile for fixing load-stop bars and straps
- Additional rear and side doors for transportation at -20°C
- Customizable setups upon request
- Aerodynamic recessed installation of cooling unit over the cabin

