Renault Master

PolarLine® by Novaplast

Fast & Easy installation

Food delivery, catering and biomedical transport

MADE IN ITALY

NOVAPLAST®
thermo-insulated solutions

UNI EN ISO 9001 : 2015
UNI EN ISO 14001 : 2015

MANUFACTURER Cemafroid

kiwa CERTIFIED ISO 9001

kiwa CERTIFIED ISO 14001

PRODUCT CERTIFICATION ACCREDIA

Renault Master

PolarLine®
NOVAPLAST
thermo-insulated solutions

	L2H2	L3H2
Roof	H2	H2
Wheelbase (mm)	3585	4215
Volume (m3)	7,5	9,16
Load floor length (mm)*	2830	3460
Load floor width (mm)*	1380/1690	1380/1690
Load floor height (mm)*	1730	1730
Side door width (mm)	1190/1230	1190/1230
Side door height (mm)	1640	1640
Rear door width (mm)	1170/1370	1170/1370
Rear door height (mm)	1590	1590
Width between wheel arches	1220	1220

*(min/max)

FEATURES

- Polyurethane foam panels, thickness 60mm for transport IN (0°C+4°C)
- Wood-reinforced floor
- Grey non-skid “tub” floor
- Reinforced roof for refrigeration unit application
- Double seal on rear and side doors

Polyurethane foam panels, thickness 80 mm for transport IR (-20°C)

ACCESSORIES

- LED lights
- Walls reinforced for shelves
- Roof and wall construction for transporting meats with stainless steel rails and hooks
- Drain valve with drain pipe
- Anti-drip edges on the doors
- Cargo restraint profiles with straps
- Additional rear and side doors (-20 °C)
- Customizable setups upon request

info@novaplastpg.it
www.novaplastpg.it