

Toyota Proace City

PolarLine[®]
by Novaplast



Food delivery,
catering and biomedical transport



Fast & Easy
installation



NOVAPLAST[®]
thermo-insulated solutions

UNI EN ISO 9001:2015
UNI EN ISO 14001:2015



	Standard	Maxi
Wheelbase (mm)	2785	2975
Roof	Low	Low
Volume (m3)	2	2,5
Load floor length (mm)	1600	1940
Load floor width (mm)	1040/1250	1040/1250
Load floor height (mm)	1090	1090
Side door width (mm)	420/560	420/560
Side door height (mm)	910	910
Rear door width (mm)	960/1100	960/1100
Rear door height (mm)	1020	1020
Width between wheel arches	1100	1100

FEATURES

- Polyurethane foam panels, thickness 60mm
- Wood-reinforced floor
- Grey non-skid "tub" floor
- Reinforced roof for refrigeration unit application
- Double seal on rear and side doors
- Suitable for IR transport (-20°C) with the application of high density polyurethane

ACCESSORIES

- LED lights
- Walls reinforced for shelves
- Roof and wall construction for transporting meats with stainless steel rails and hooks
- Drain valve with drain pipe
- Anti-drip edges on the doors
- VTR liquid collection reservoir
- Cargo restraint profiles with straps
- IR rear and side supplementary doors (-20 °C)
- Customizable setups upon request

